

# SIMSON<sup>®</sup> POLYMEER

## DECLARATION OF PERFORMANCE



### DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Product Regulation)

**DoP-nr. 200803-01**

1. Unique identification code of product-type:  
**SIMSON POLYMEER**
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**Batch number: see product packaging**
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
Sealants for façade elements  
Sealants for pedestrian walkways  
**EN 15651-1: F-EXT-INT-CC (CLASS 25LM)**  
**EN 15651-4: PW-EXT-INT-CC (CLASS 25LM)**
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):  
**SIMSON APPLICATIE B.V. | DE KREEK 1 | 4906 BB OOSTERHOUT (NB) NL**
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): **not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3**  
**System 3 for reaction to fire**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-4 and reaction to fire under system 3 and issued a: test report.**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **not relevant**



# SIMSON<sup>®</sup> POLYMEER

## DECLARATION OF PERFORMANCE

### 9. Declared performance

Conditioning: Procedure B (according to ISO 8340)  
Substrate: Mortar M1 (with primer P03)  
Anodised aluminium (without primer)

ESSENTIËLE CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Reaction to fire	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
<b>Water tightness and air tightness</b>		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	≤ 0,9 MPa	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
<b>Durability</b>	Pass	

Substrate: Mortar M1 (with primer P03)

ESSENTIËLE CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Reaction to fire	Class E	EN 15651-4:2012
Release of chemical dangerous to the environment and health	NPD (*)	
<b>Water tightness and air tightness</b>		
Tensile properties at maintained extension	NF	
Loss of volume	≤ 10 %	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus: ≤ 50 %	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	≤ 0,9 MPa	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
<b>Durability</b>	Pass	

(\*) See material safety data sheet  
NPD: No Performance Determined  
NF: No Failure



# SIMSON<sup>®</sup> POLYMEER

## DECLARATION OF PERFORMANCE

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Erik van der Meijden  
Simson Applicatie B.V.  
Oosterhout, 07/2020

